

USB to Serial Converter PL2303 Chipset



Description

The USB to Serial Converter Cable is ideal for connecting RS232 devices to any of the PhidgetSBC's USB ports.

The SBC will automatically recognize the Converter when it is plugged in and will create a serial port for it.

Be aware that the SBC4205 and any serial devices connected to it are not "Phidgets devices" and therefore cannot be accessed or controlled by the Phidgets' APIs. Using this product requires a working knowledge of Linux

Product Specifications

Physical Properties

Connector A	USB Type-A (Male)
Connector B	RS-232 DB-9 (Male)
Cable Length	960 mm

Converter

I/O Communication Protocol USB 1.1 and USB CDC 1.1

Data Rate Max	1 Mbit/s
Buffer Size	96 B

Electrical Properties

Current Consumption Max	32 mA
-------------------------	-------

Customs Information

Canadian HS Export Code	8473.30.00
American HTS Import Code	8473.30.51.00
Country of Origin	TW (Taiwan)

Connector A	USB Type-A (Male)
Connector B	RS-232 DB-9 (Male)
Cable Length	960 mm

Converter

I/O Communication Protocol USB 1.1 and USB CDC 1.1

Data Rate Max	1 Mbit/s
---------------	----------

Buffer Size	96 B
-------------	------

Electrical Properties

Current Consumption Max	32 mA
-------------------------	-------

Customs Information

Canadian HS Export Code	8473.30.00
-------------------------	------------

American HTS Import Code	8473.30.51.00
--------------------------	---------------

Country of Origin	TW (Taiwan)
-------------------	-------------