<u>Differential Air Pressure Sensor 100</u> kPa



Product Description

Note: The 1139_0B is identical to the 1139_0, except that you have the option of which size of Phidget cable to include.

The 1139 Differential Pressure Sensor is a dual ported air pressure sensor that measures the pressure difference between the two ports. It can measure pressure from 0 kPa to 100 kPa.

Warning



This sensor is designed to measure the pressure of clean, non-condensing air. Contact with moist air (i.e, human breath), dusty air, or other gases can damage the sensor.

Product Specifications

Product Specifications

Sensor Properties

Sensor Type	Gas Pressure (Differential)
Controlled By	VoltageRatio Input
Sensor Output Type	Ratiometric
Pressure Differential Min	0 Pa
Pressure Differential Max	100 kPa
Case Pressure Max	400 kPa
Pressure Resolution	111 Pa
Measurement Error Max	± 2.5 %
Warm-up Time	20 ms

Response Time Max	1 ms	
Electrical Properties		
Supply Voltage Min	4.8 V DC	
Supply Voltage Max	5.3 V DC	
Current Consumption Max	10 mA	
Output Impedance	1 kΩ	
Output Voltage Min	250 mV DC	
Output Voltage Max	4.8 V DC	
Physical Properties		
Operating Temperature Min	-40 °C	
Operating Temperature Max	125 °C	
Recommended Tubing Size	3∏32″	
Customs Information		
Canadian HS Export Code	8473.30.00	
American HTS Import Code	8473.30.51.00	
Country of Origin	CN (China)	